

MIRO ONE -PACK EPOXY



Miro One-Pack Epoxy Primer Can Be Applied On Mild Steel, Stainless Steel, and Aluminium Surfaces Under Moderate To High Humid Conditions. Its Excellent Adhesion Property Makes It A Long Durable Anti Rust Finish. It can be applied to both interior and exterior surfaces.

SALIENT FEATURES



**SINGLE PACK
WITHOUT HARDENER**



**ANTI-CORROSIVE
PROTECTION**



**DIRECT APPLICATION
ON METAL SURFACES**



**FREE FROM VOC
AND LEAD**



**QUICK
DRYING**

APPLICATION PROCESS

- **Step 1:** Get rid of any rust, grime, oil, or grease before painting. Eliminate oil, grease, and other impurities with the appropriate thinner.
- **Step 2:** To make sure the surface is clean and smooth, scrub it with a wire brush or Sandpaper No. 150 or 180. Verify that the surface is completely dry and clean.
- **Step 3:** Take the necessary amount of Miro anticorrosive one-pack epoxy primer (Thinning of this epoxy primer is not recommended. However, depending on conditions, it can be thinned up to a maximum of 6 -7% with a suitable epoxy or NC-based thinner)
- **Step 4:** Apply 1st coat of epoxy primer.
- **Step 5:** After applying the first layer of primer, give it 4 to 6 hours to dry. -
- **Step 6:** Use Sandpaper No. 120/180 to sand the primed surface, then wipe it clean before applying 2nd coat.
- **Step 7:** Apply the second primer coat.
- **Step 8:** Sand/Emery Paper No. 320 and 600 should then be used to dry cut the surface.
- **Step 9:** Then, follow it up with the application of a topcoat of enamel paint(optional)

ADDITIONAL INFORMATION

Post Painting Care For The Best Performance Of The Paint, Ensure Proper Cleaning Of All Dust, Oil And External Particles, If Any, At Regular Intervals Of Six Months.

PRODUCT FEATURES

WASHABILITY



EXCELLENT

AVAILABLE
PACK SIZES



100 ML



500 ML



1 LTR

SHELF
LIFE

36 MONTHS FROM THE
DATE OF MANUFACTURING

COLORS
AVAILABLE

02 SHADES GREY & BLACK

FINISH

SATIN

COVERAGE



12-14*

Sq Mtr/Litre/Coat

(ACTUAL COVERAGE WILL HOWEVER VARY DEPENDING UPON
THE NATURE / POROSITY OF THE SUBSTRATE.)

SAFETY



- Please refer to the MSDS for Miro one-pack Epoxy Primer, which is available upon request and provides comprehensive information on safety precautions to take when handling the paint.
- Keep the product away from sources of ignition and fire and at room temperature in areas with adequate ventilation.
- Do not apply when the ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of this application.
- If there is contact between the skin and eyes, wash with lots of clean water.
- Avoid ingestion or inhalation.
- Move to fresh air if you inhale, and get medical help if the symptoms persist in both situations.
- When working with paint, wear protective gear such as face masks, safety goggles or glasses, and rubber or polyethylene gloves.
- Before using, give it a good stir and strain.